

EXCLUSIVE RANGE — Solid bamboo flooring with exceptional density, 3 crossed layers

F13BONA140

- Dimensions:** 13 x 140 x 1850 mm
- Coating:** Mass colored - Factory applied WOCA oil layer - matt appearance
- Color:** Nairobi (caramel with black flames)
- Chamfer:** GO2
- Installation:** Glued: Yes
Floating: No
Floorheating and cooling: Yes if glued
Use in bathroom: Yes if glued
- Wearing surface:** 3 mm
- Box :** Content: 8 planks/box (2,072 m²)
Weight: 26.64 kg
- Maintenance :** cfr maintenance instructions



BRINELL HARDNESS	8,5 N/mm ² - EN 1534 norm (Report CTIB 5229/2)
CONTRACTION COEFFICIENT	0,14% per % humidity variation
HUMIDITY DEGREE	10% at 20 °C and 65% relative humidity 8% at 20 °C and 50% relative humidity
DENSITY	1100 kg/m ³
FIRE NORM	CFLS1 if glued
FORMALDEÉHYDE EMISSION	0,04 mg/ m ² h - EN 717-2 norm (Report CTIB 5229/2)
THERMISCHE WEERSTAND	0,072 m ² ·K/W - EN 12664 norm (Report CTIB 5229/2)
PCP CONTENT	Below detection limit (Report CTIB 5229/2)
VOC FREE	Below detection limit – EN 15052 norm

Do not forget the accessories!

