





Our "BamWood®" flooring is made from bamboo strips assembled under very high pressure, giving it a noble and elegant appearance. The planks are finished in the factory, either with a UV varnish with a matt appearance or with Woca® oil, also with a matt appearance. Beyond its beauty, Bamwood® is exceptionally hard and resistant to wear and impact. Several types of installation are available for all uses. Most can be used for bathrooms and underfloor heating. The quality of our products allows us to offer a warranty of up to 30 years on condition that the installation is done according to our instructions, respecting the norms in effect in the country and following our maintenance recommendations.



Available colors :



Champagne

Gold

Camel

Caramel

Nairobi

Reference	Coating ¹	Color	Glued pose	Floating pose	Floor heating ³	Bath-room ³	Dimensions (mm)	Wear layer (mm)	Under layer	Structure	Bevel	Inter-locking ²	Content box
F10BCC60	V	Caramel	✓	✓	✓	✓	10x60x920	±4	No	Solid	GO2	T/G	1,77m ² 18kg
F10BIC200	B	Caramel	✓	X	✓	✓	10x200x300	±10	No	Solid	-	-	1,92m ² 19kg
F10BCC130	V	Caramel	✓	✓	✓	✓							
F10BOC130	H	Caramel	✓	✓	✓	✓							
F10BCCH130	V	Champagne	✓	✓	✓	✓	10x130x915	±4	No	Solid	GO2	T/G	1,9m ² 19kg
F10BOCH130	H	Champagne	✓	✓	✓	✓							
F10BCG130	V	Gold	✓	✓	✓	✓							
F10BCCA130	V	Camel	✓	✓	✓	✓							
F10BOCBR95	H	Caramel	✓	X	✓	✓	10x95x855	±4	No	Solid	GO2	T/G	1,95m ² 20kg
F10BOCHBR122	H	Champagne	✓	X	✓	✓	10x122x610	±4	No	Solid	GO2	T/G	1,79m ² 21kg
F12BCC142	V	Caramel	✓	✓	✓	✓							
F12BOCH142	H	Champagne	✓	✓	✓	✓	12x142x1850	±4	No	Solid	GO2	T/G	2,1m ² 25kg
F12BCG142	V	Gold	✓	✓	✓	✓							
F12BCCA142	V	Camel	✓	✓	✓	✓							
F7SBCC130	V	Caramel	X	✓	✓ ⁶	✓							
F7SBCCA130	V	Camel	X	✓	✓ ⁶	✓	6/1x130x920	±1	Inclusif (IXPE)	SPC	mini	Click	1,43m ² 18kg
F7SBCH130	V	Champagne	X	✓	✓ ⁶	✓							
F7SBG130	V	Gold	X	✓	✓ ⁶	✓							
F10BCCL125	V	Caramel	X	✓	X	X							
F10BCHCL125	V	Champagne	X	✓	X	X	10x125x920	±2,5	No	HDF	GO2	Click	1,38m ² 12kg
F10BGCL125	V	Gold	X	✓	X	X							
F10BCCACL125	V	Camel	X	✓	X	X							
F14BMCC190	V	Caramel	✓	✓	✓	✓							
F14BMCH190	V	Champagne	✓	✓	✓	✓	14/3x190x1850	±4	No	Multiply	GO2	T/G	2,11m ² 17kg
F14BMGC190	V	Gold	✓	✓	✓	✓							
F14BMCCA190	V	Camel	✓	✓	✓	✓							
F15BMOC208	H	Caramel	✓	✓	✓	✓	15x208x1850	±4	No	Multiply	GO2	T/G	2,31m ² 25kg
F15BMOCH208	H	Champagne	✓	✓	✓	✓							
F13BONA140	H	Nairobi	✓	✓	✓	✓	13x140x1850	±3	No	3 crossed Layers bb	GO2	T/G	2,07m ² 27kg
F13BCNA140	V	Nairobi	✓	✓	✓	✓							

¹ V= varnishes / H= oil / B= Unfinished

² T/G = Tongue/Groove

³ In case of floating installed, without click system, the tongue must be glued in the groove.

⁴ Installation on floorheating is ideally glued. Floating installation creates an insulating layer of air that reduces the performance of underfloor heating.

⁵ Bathroom installation **must be glued** (except for SPC). Extreme care must be taken to ensure a watertight seal around the perimeter.

⁶ BSPC can be installed on underfloor heating as a floating system, but is not recommended (see point 4 above).

Installation advice available on our website www.bambootouch.com/en/advice.

nv Pi-Import sa

Av du Commerce 33

1420 Braine-l'Alleud – Belgium



info@bambootouch.com

www.bambootouch.com

Tel. : +32 (0)2 384 58 77





Storage, installation and maintenance requirements (DTU 51.2 or local standard and according to type of installation)

- Planks should be stored horizontally at a temperature of 15 to 25°C and relative humidity of 45 to 65%.
- The flooring requires acclimatization and will be left 48h in its open packaging on the place of installation..
- Bamboo is a natural product. Variations in color, grain or shine are normal. Be sure to mix the planks from different packages before installation. **All installed flooring will be considered accepted.**
- The screed must be dry, clean and even. The moisture content, evenness and load-bearing capacity of the screed must be in accordance with current standards. Residual moisture must not exceed 2.7%.
- Allow for an expansion gap of +/- 1 cm around the floor and obstacles.
- Provide a divider joint every 8 to 10m.
- Splits and fiber separation are possible on oiled products. This phenomenon is natural and is no reason for warranty claim. A (light) sanding and oiling will reduce them.
- Blanchon® oil is not compatible with our oiled floorings.
- Installation, cleaning and maintenance instructions are available on our website www.bambootouch.com/en/advice





Technical specifications

- Brinell hardness: $\pm 9 \text{ kg/mm}^2$ (EN 1534 – CTIB 5229/2)
- Contraction coefficient: 0,14% per % of humidity variation
- Humidity level : 10% at 20° and 65% of relative humidity
8% at 20° and 50% of relative humidity
- Density : $\pm 1.050 \text{ kg/m}^3$
- Fire standard : CFLS1 if glued pose BFLS1 for some products
- Formaldehyde emissions: $E0 < 0,008 \text{ mg/m}^2\text{h}$ (EN 717-2 CTIB DE670X417 and EN 16000-9)
- PCP level : below detection limit (CTIB 5229/2)
- VOC Free : sous la limite de détection (EN15052 CTIB 5229/2)
- Thermal resistance : $0,05 \text{ m}^2\text{K/W}$ (EN12664 CTIB 5229/2)
- Thermal conductivity : $0,20 \text{ W/mK}$
- Warranty: up to 30 years under conditions (see our website)

Accessories varnished flooring

		Caramel	Camel	Gold	Champagne	Dimensions
Wallbase/Stairnose		AWB14BCC88				14 x 88 x 1860 mm
			AWB14BCCA70	AWB14BCG70	AWB14BCCH70	14 x 70 x 1860 mm
Wallbase low		AW14BCC50				14 x 50 x 1860 mm
¼ round		AQR15BCC15				15 x 15 x 1860 mm
Reducer		ARE14BCC56				14 x 56 x 1860 mm
T Profile		ATM15BCC50		ATM15BCG50		15 x 50 x 1860 mm

Accessories oiled flooring

		Caramel	Champagne	Nairobi	Dimensions
Wallbase/Stairnose		AWB14BOC88	AWB14BOCH70		14 x 88 x 1860 mm
				AWB13BONA88	13 x 88 x 1860 mm
¼ round			AQR15BOCH15		15 x 15 x 1860 mm
Reducer		ARE14BOC56			14 x 56 x 1860 mm
T Profile			ATM15BOCH50	ATM15BONA50	15 x 50 x 1860 mm